PRODUCT INFORMATION

Description 12-24V DOT LED High & Low Beam

Headlight

 Height
 142.24 mm / 5.6 in

 Width
 142.24 mm / 5.6 in

 Depth
 86.36 mm / 3.4 in

Shape Round

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Die Cast Aluminum

Housing ColorBlackBezel ColorBlack

Minimum Operating -34 °C / -29.2 °F

Temperature

 $\textbf{Maximum Operating} \hspace{1.5cm} 49~^{\circ}\text{C}~/~120.2~^{\circ}\text{F}$

Temperature


Connector or Wiring Integral Connector in Housing simulating

Delphi 12124107

Mating ConnectorDelphi 12052848Product Weight1.76 lbs / 0.8 kgsShipping Weight1.80 lbs / 0.82 kgs



PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS


Input Voltage12-24V DCOperating Voltage10-32V DC

Transient Spike Protection 150V Peak @ 1 HZ-100 Pul

Yellow Wire Low Beam
White Wire High Beam
Black Wire Ground

Current Draw 2.20A @ 12V DC (Low Beam)

1.70A @ 14V DC (Low Beam) 1.10A @ 24V DC (Low Beam) 3.50A @ 12V DC (High Beam) 2.70A @ 14V DC (High Beam) 1.70A @ 24V DC (High Beam)





REGULATORY STANDARDS COMPLIANCE









Buy America Standards FMVSS 108 Table XIX IEC IP67

Eco Friendly FMVSS 108 Table XVIII

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 2,925 (High Beam); 2,025 (Low

Beam)

Effective Lumen

Output

1,000 (High Beam); 630 (Low Beam)

Candela Output 61, 684 (High Beam); 19,162 (Low

Beam) 5000 K

Nominal LED Color


Temperature

Beam Pattern(s)

Forward Lighting - High Beam

(DOT/ECE)

Forward Lighting - Low Beam (DOT)



APPLICATIONS















ACCESSORIES





Double Ring Kit Mounting Assembly for LED Headlight Model 8630



Part Number 8200001

Single Ring Kit Mounting Assembly for LED Headlight Model

RELATED PRODUCTS



Part Number 0549911

12-24V DOT/ECE LED RHT High & Low Beam Headlight with FP & DRL



Part Number 0549921

12-24V ECE LED LHT High & Low Beam Headlight with FP & DRL

Print date: 2017-10-23