

# LED Headlights – Model 8632 Evolution

## PRODUCT INFORMATION

<b>Description</b>	12-24V DOT/ECE LED RHT Left Hand High & Low Beam Headlight with Turn Signal, FP & DRL
<b>Height</b>	173.00 mm / 6.81 in
<b>Width</b>	144.00 mm / 5.67 in
<b>Depth</b>	86.00 mm / 3.39 in
<b>Shape</b>	Round
<b>Outer Lens Material</b>	Polycarbonate
<b>Outer Lens Color</b>	Clear
<b>Housing Material</b>	Aluminum
<b>Housing Color</b>	Black
<b>Mounting Type</b>	Pedestal
<b>Minimum Operating Temperature</b>	-34 °C / -29.2 °F
<b>Maximum Operating Temperature</b>	49 °C / 120.2 °F
<b>Connector or Wiring</b>	Integral Connector in Housing simulating Delphi 12124107,
<b>Mating Connector</b>	Delphi 12052848
<b>Product Weight</b>	0.00 lbs / 0 kgs
<b>Shipping Weight</b>	2.60 lbs / 1.18 kgs



Print date: 2018-11-13

© 2018 J.W. Speaker Corporation • Germantown, WI U.S.A.  
 www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

**J.W. SPEAKER**   
 Engineered. Lighting. Solutions.

# LED Headlights – Model 8632 Evolution

## PRODUCT DIMENSIONS



## ELECTRICAL SPECIFICATIONS


<b>Input Voltage</b>	12-24 V
<b>Operating Voltage</b>	10-32 V
<b>Transient Spike Protection</b>	150V Peak @ 1 HZ-100 Pul
<b>White Wire</b>	High Beam
<b>Yellow Wire</b>	Low Beam
<b>Black Wire</b>	Ground
<b>Red Wire</b>	Front Position
<b>Purple Wire</b>	DRL
<b>Orange/white Wire</b>	Front Turn
<b>Current Draw</b>	3.67A @ 12V (High Beam) 1.83A @ 24V (High Beam) 2.5A @ 12V (Low Beam) 1.25A @ 24V (Low Beam) .67A @ 12V (DRL) .34A @ 24V (DRL) .83A @ 12V (Front Turn) .42A @ 24V (Front Turn) .08A @ 12V (Front Position) .042A @ 24V (Front Position) .08A @ 12V (Side Marker) .042A @ 24V (Side Marker)

Print date: 2018-11-13

© 2018 J.W. Speaker Corporation • Germantown, WI U.S.A.  
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

# LED Headlights – Model 8632 Evolution


## REGULATORY STANDARDS COMPLIANCE



- |                     |                       |
|---------------------|-----------------------|
| ECE Reg 112         | ECE Reg 6             |
| ECE Reg 7           | ECE Reg 87            |
| FMVSS 108 Table VI  | FMVSS 108 Table X     |
| FMVSS 108 Table XIX | FMVSS 108 Table XVIII |
| IEC IP67            | SAE J1395             |
| SAE J2087           | SAE J222              |

## PHOTOMETRIC SPECIFICATIONS

- Raw Lumen Output** 2,925 (High Beam); 2,025 (Low Beam)
- Effective Lumen Output** 1,000 (High Beam); 630 (Low Beam)
- Nominal LED Color Temperature** 5000 K
- Beam Pattern(s)** Forward Lighting - Daytime Running Light  
Forward Lighting - High Beam (DOT/ECE)  
Forward Lighting - Low Beam (DOT/ECE)  
Signalization - Front Position  
Signalization - Marker  
Signalization - Turn (Front)



Print date: 2018-11-13

© 2018 J.W. Speaker Corporation • Germantown, WI U.S.A.  
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660



# LED Headlights – Model 8632 Evolution

## APPLICATIONS



## RELATED PRODUCTS



**Part Number**  
**0551561**  
12-24V DOT/ECE LED  
RHT Right Hand High &  
Low Beam Headlight  
with Turn Signal, FP &  
DRL



**Part Number**  
**0551973**  
12-24V ECE LED LHT  
High & Low Beam  
Headlights with Turn  
Signal, FP & DRL - 2  
Light Kit



**Part Number**  
**0551983**  
12-24V DOT/ECE LED  
RHT High & Low Beam  
Headlights with Turn  
Signal, FP & DRL - 2  
Light Kit



**Part Number**  
**0551991**  
12-24V ECE LED LHT  
Right Hand High & Low  
Beam Headlight with  
Turn Signal, FP & DRL



**Part Number**  
**0552001**  
12-24V ECE LED LHT  
Left Hand High & Low  
Beam Headlight with  
Turn Signal, FP & DRL