LED Signal Lights - Model 206

PRODUCT INFORMATION

Description 12-24V SAE Double-Sided LED Turn

Signal with Guard

 Height
 124.71 mm / 4.91 in

 Width
 124.71 mm / 4.91 in

 Depth
 23.11 mm / 0.91 in

Shape Round

Outer Lens Material Polycarbonate

Outer Lens Color Amber

Housing Material Polycarbonate

Housing Color Black

Mounting Type Hollow Stud Mount **Minimum Operating** -40 °C / -40 °F

Temperature

Maximum Operating 65 °C / 149 °F

Temperature

Connector or Wiring12" Bare LeadsProduct Weight0.62 lbs / 0.28 kgsShipping Weight0.91 lbs / 0.41 kgs



ELECTRICAL SPECIFICATIONS

Input Voltage12-24V DCRed WirePositiveBlack WireNegative

Current Draw 0.575A @ 12V DC

0.267A @ 24V DC



LED Signal Lights - Model 206

REGULATORY STANDARDS COMPLIANCE











ASABE S279 Eco Friendly SAE J974

Buy America Standards IEC IP67

PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s) Signalization - Turn (Front)

Signalization - Turn (Rear)

APPLICATIONS



















PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

Print date: 2024-05-08



LED Signal Lights - Model 206

RELATED PRODUCTS



Part Number 0341681 12-24V SAE Double-Sided LED Turn Signal without Guard



Part Number 0342771 12-24V ECE/SAE Single-Sided LED Stop & Tail Light without Guard



Part Number 0342781 12-24V ECE/SAE Single-Sided LED Stop & Tail Light with Guard