

LED Signal Lights - Model 206

PRODUCT INFORMATION

| | |
|--------------------------------------|--|
| Description | 12-24V SAE Double-Sided LED Turn Signal with Guard |
| Height | 124.71 mm / 4.91 in |
| Width | 124.71 mm / 4.91 in |
| Depth | 23.11 mm / 0.91 in |
| Shape | Round |
| Outer Lens Material | Polycarbonate |
| Outer Lens Color | Amber |
| Housing Material | Polycarbonate |
| Housing Color | Black |
| Mounting Type | Hollow Stud Mount |
| Minimum Operating Temperature | -40 °C / -40 °F |
| Maximum Operating Temperature | 65 °C / 149 °F |
| Connector or Wiring | 12" Bare Leads |
| Product Weight | 0.62 lbs / 0.28 kgs |
| Shipping Weight | 2.20 lbs / 1 kgs |



ELECTRICAL SPECIFICATIONS

| | |
|----------------------|------------------------------------|
| Input Voltage | 12-24V DC |
| Red Wire | Positive |
| Black Wire | Negative |
| Current Draw | 0.575A @ 12V DC 0.267A @ 24V DC |

Print date: 2018-09-24

© 2018 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

LED Signal Lights - Model 206

REGULATORY STANDARDS COMPLIANCE



ASABE S279
Eco Friendly
SAE J974

Buy America Standards
IEC IP67

PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s) Signalization - Turn (Front)
 Signalization - Turn (Rear)

APPLICATIONS



RELATED PRODUCTS



Part Number
0341681
12-24V SAE Double-Sided LED Turn Signal without Guard



Part Number
0342771
12-24V ECE/SAE Single-Sided LED Stop & Tail Light without Guard



Part Number
0342781
12-24V ECE/SAE Single-Sided LED Stop & Tail Light with Guard

Print date: 2018-09-24

© 2018 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660