# Model 775 L Work Light

#### **PRODUCT INFORMATION**

**Description** 12-48V LED Work Light with Spot Beam

& Turn Signal

 Height
 180.34 mm / 7.1 in

 Width
 99.57 mm / 3.92 in

 Depth
 58.42 mm / 2.3 in

**Shape** Oval

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing Color Black

**Mounting Hardware** (x1) 5/16"-18 x 1.00" Mounting Bolt

Description

Mounting Type Universal Pedestal Mount

**Minimum Operating**  $-40 \, ^{\circ}\text{C} \, / \, -40 \, ^{\circ}\text{F}$ 

**Temperature** 

**Maximum Operating** 65 °C / 149 °F

**Temperature** 

**Connector or Wiring** 2-Pin Deutsch Weather-Proof Plug

(DT06-2S)

**Product Weight** 0.85 lbs / 0.39 kgs **Shipping Weight** 7.34 lbs / 3.33 kgs



**Input Voltage** 12-48V DC **Operating Voltage** 9-60V DC

**Transient Spike Protection** 330V Peak @ 1 HZ-100 Pulses

Black WireGroundWhite WireWorklightRed WireParkYellow WireTurn

Current Draw 1.2A @ 12V DC

0.6A @ 24V DC 0.4A @ 36V DC 0.3A @ 48V DC





# Model 775 L Work Light

## REGULATORY STANDARDS COMPLIANCE









Buy America Standards CISPR 22 Eco Friendly

CISPR 12 ECE Reg 6 IEC IP67

**UL** Recognized

#### PHOTOMETRIC SPECIFICATIONS

5000 K

Raw Lumen Output 600 **Effective Lumen** 400

Output

**Nominal LED Color** 

**Temperature** 

Beam Pattern(s) Forward Lighting - Spot

Spot Beam (2.5m high at -5°) 60m 30m 10+ Lux 1 Lux 0m 30m 0.25 Lux 60m 50m 100m 150m

### **APPLICATIONS**




























# Model 775 L Work Light

#### **PRODUCT WARNINGS**

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

**AVERTISSEMENT:** Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

## **RELATED PRODUCTS**



<u>Part Number</u> <u>1707191</u>

12-48V Amber Clear LED Work Light with Flood Beam & Turn Signal

