### **PRODUCT INFORMATION**


Description	12-24V LED Work L Pattern
Height	154.18 mm / 6.07 i
Width	113.28 mm / 4.46 ii
Depth	54.10 mm / 2.13 in
Shape	Square
<b>Outer Lens Material</b>	Polycarbonate
Outer Lens Color	Clear
Housing Material	Polycarbonate
Housing Color	Black
Mounting Hardware Description	(x1) 5/16"-18 x 1.00
Mounting Type	Universal Pedestal
Minimum Operating Temperature	-40 °C / -40 °F
Maximum Operating Temperature	65 °C / 149 °F
Connector or Wiring	Integrated 2-Pin De Socket (DT04-2P)
Mating Connector	2-Pin Deutsch Weat (DT06-2S)
Product Weight	0.86 lbs / 0.39 kgs
Shipping Weight	1.30 lbs / 0.59 kgs

12-24V LED Work Light with Flood Beam Pattern
154.18 mm / 6.07 in
113.28 mm / 4.46 in
54.10 mm / 2.13 in
Square
Polycarbonate
Clear
Polycarbonate
Black
(x1) 5/16"-18 x 1.00" Mounting Bolt
Universal Pedestal Mount
-40 °C / -40 °F
65 °C / 149 °F
Integrated 2-Pin Deutsch Weather-Proof Socket (DT04-2P)
2-Pin Deutsch Weather-Proof Plug (DT06-2S)
0.86 lbs / 0.39 kgs





### **PRODUCT DIMENSIONS**



## **ELECTRICAL SPECIFICATIONS**

Input Voltage	12-24V DC			
Operating Voltage	10-30V DC			
Transient Spike Protection	330V Peak @ 1 HZ-100 Pulses			
Red Wire	Positive			
Black Wire	Negative			
Current Draw	1.25A @ 12V DC 0.61A @ 24V DC			



## **REGULATORY STANDARDS COMPLIANCE**



Buy America StandardsCISPR 12CISPR 22Eco FriendlyIEC IP69KSAE J1113-13Tested to ECE Reg. 10UL Recognized(Radiated Emissions only)Vertical Addressions

#### **PHOTOMETRIC SPECIFICATIONS**

Raw Lumen Output	1,080 780		20	Flood Beam (2.5m high at -15°)	
Effective Lumen Output			30m		
Nominal LED Color Temperature	5000 K	10+ Lux	15m		
Beam Pattern(s)	Forward Lighting - Flood (Standard)	1 Lux 0.25 Lux	0m		
	0.23 Lux	30m			

#### **APPLICATIONS**



Print date: 2024-04-20 © 2024 J.W. Speaker Corporation • Germantown, WI U.S.A. www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660



50m

25m

75m

#### **PRODUCT WARNINGS**

For California residents: ▲ WARNING: Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>. ▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - <u>www.P65Warnings.ca.gov</u>.

#### ACCESSORIES







Part Number 8200101 or Stainless Steel hts Mounting Kit for Work Lights & Marine Lights



Part Number 8200491 Mounting Kit For Work Lights



#### **RELATED PRODUCTS**



**Part Number** 1300011 with Trapezoid Beam Pattern



**Part Number** 1300021 12-24V LED Work Light 12-24V LED Work Light 12-110V LED Work with Spot Beam Pattern



**Part Number** 1300031 Light with Trapezoid Beam Pattern & Integrated 2-Pin Deutsch Connector



**Part Number** 1300041 12-110V LED Work Light with Trapezoid Beam Pattern & Integrated AMP Connector



**Part Number** 1300091 12-110V LED Work Light with Flood Beam Pattern



**Part Number** 1300101 12-110V LED Work Light with Spot Beam Pattern



**Part Number** 1300301 12-48V LED Work Light 12-48V LED Work Light with Left Hand Vertical Flood Beam Pattern



**Part Number** 1300311 with Right Hand Vertical Flood Beam Pattern

