

Model BOBCAT GEN 5 LED Work Light

PRODUCT INFORMATION

Description	12V Gen 5 Bobcat LED Flood Headlight, LH & RH Kit
Height	174.00 mm / 6.85 in
Width	189.00 mm / 7.44 in
Depth	152.00 mm / 5.98 in
Shape	Stylized
Outer Lens Material	Polycarbonate
Outer Lens Color	Clear
Housing Material	Nylon
Housing Color	Black
Minimum Operating Temperature	-40 °C / -40 °F
Maximum Operating Temperature	65 °C / 149 °F
Mating Connector	PE 12124819
Product Weight	1.17 lbs / 0.53 kgs
Shipping Weight	3.00 lbs / 1.36 kgs



BOBCAT RIGHT HAND FLOOD HEADLIGHT

BOBCAT LEFT HAND FLOOD HEADLIGHT

ELECTRICAL SPECIFICATIONS

Input Voltage	12V DC
Operating Voltage	10 - 16V DC
Transient Spike Protection	150V Peak @ 1 HZ-100 Pul
Current Draw	1.50A @ 12V DC (Flood)

REGULATORY STANDARDS COMPLIANCE



IEC IP67

Print date: 2020-11-24

© 2020 J.W. Speaker Corporation • Germantown, WI U.S.A.
 www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER
 Engineered. Lighting. Solutions.

Model BOBCAT GEN 5 LED Work Light

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output	1728
Effective Lumen Output	1050
Nominal LED Color Temperature	5000 K
Beam Pattern(s)	Forward Lighting - Flood (Medium)

PRODUCT WARNINGS

For California residents:

⚠ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

⚠ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number
0557621

12V Gen 5 Bobcat LED
Flood Headlight, LH



Part Number
0557631

12V Gen 5 Bobcat LED
Flood Headlight, RH

Print date: 2020-11-24

© 2020 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660