

# Model BOBCAT GEN 5 LED Work Light

## PRODUCT INFORMATION

<b>Description</b>	12V Gen 5 Bobcat LED Flood Headlight, RH
<b>Height</b>	174.00 mm / 6.85 in
<b>Width</b>	189.00 mm / 7.44 in
<b>Depth</b>	152.00 mm / 5.98 in
<b>Shape</b>	Stylized
<b>Outer Lens Material</b>	Polycarbonate
<b>Outer Lens Color</b>	Clear
<b>Housing Material</b>	Nylon
<b>Housing Color</b>	Black
<b>Minimum Operating Temperature</b>	-40 °C / -40 °F
<b>Maximum Operating Temperature</b>	65 °C / 149 °F
<b>Mating Connector</b>	PE 12124819
<b>Product Weight</b>	1.17 lbs / 0.53 kgs
<b>Shipping Weight</b>	1.65 lbs / 0.75 kgs



## ELECTRICAL SPECIFICATIONS

<b>Input Voltage</b>	12V DC
<b>Operating Voltage</b>	10 - 16V DC
<b>Transient Spike Protection</b>	150V Peak @ 1 HZ-100 Pulses
<b>Current Draw</b>	1.50A @ 12V DC (Flood)

## REGULATORY STANDARDS COMPLIANCE



IEC IP67

Print date: 2020-11-26

© 2020 J.W. Speaker Corporation • Germantown, WI U.S.A.  
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

**J.W. SPEAKER**  
Engineered. Lighting. Solutions.

# Model BOBCAT GEN 5 LED Work Light

## PHOTOMETRIC SPECIFICATIONS

---

<b>Raw Lumen Output</b>	1728
<b>Effective Lumen Output</b>	1050
<b>Nominal LED Color Temperature</b>	5000 K
<b>Beam Pattern(s)</b>	Forward Lighting - Flood (Medium)

## PRODUCT WARNINGS

---

For California residents:

⚠ **WARNING:** Cancer and reproductive harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

⚠ **AVERTISSEMENT:** Cancer et effet nocif sur la reproduction - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## RELATED PRODUCTS

---



**Part Number**  
**0557613**

12V Gen 5 Bobcat LED  
Flood Headlight, LH &  
RH Kit

**Part Number**  
**0557621**

12V Gen 5 Bobcat LED  
Flood Headlight, LH

---

**Print date: 2020-11-26**

© 2020 J.W. Speaker Corporation • Germantown, WI U.S.A.  
[www.jwspeaker.com](http://www.jwspeaker.com) • [speaker@jwspeaker.com](mailto:speaker@jwspeaker.com) • 262.251.6660