PRODUCT INFORMATION

Description	12-24 ECE LED LHT High & Low Beam Headlight with FP & Panel Mount	
Height	129.79 mm / 5.11 in	
Width	168.66 mm / 6.64 in	
Depth	87.38 mm / 3.44 in	
Shape	Rectangular	
Outer Lens Material	Polycarbonate	
Outer Lens Color	Clear	
Housing Material	Aluminum	00
Housing Color	Black	
Bezel Color	Black	
Mounting Type	Panel Mount	
Connector or Wiring	12" Flying Leads	
Product Weight	2.50 lbs / 1.13 kgs	
Shipping Weight	2.84 lbs / 1.29 kgs	

PRODUCT DIMENSIONS





ELECTRICAL SPECIFICATIONS

Input Voltage	12-24V DC
Operating Voltage	10-30V DC
Black Wire	Ground
White Wire	High Beam
Yellow Wire	Low Beam
Red Wire	Front Position
Current Draw	1.11A @ 12V DC (Low Beam) 0.96A @ 24V DC (Low Beam) 2.14A @ 12V DC (High Beam) 1.56A @ 24V DC (High Beam) 0.056A @ 12V DC (Front Position) 0.065A @ 24V DC (Front Position)

REGULATORY STANDARDS COMPLIANCE



Buy America Standards ECE Reg 7 IEC IP67

ECE Reg 112 Eco Friendly



PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output	2,100 (High Beam); 1,850 (Low Beam)
Effective Lumen Output	755 (High Beam); 645 (Low Beam)
Beam Pattern(s)	Forward Lighting - High Beam (DOT/ECE) Forward Lighting - Low Beam (ECE Left Hand) Signalization - Front Position



APPLICATIONS



PRODUCT WARNINGS

For California residents: ▲ WARNING: Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>. ▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - <u>www.P65Warnings.ca.gov</u>.

Print date: 2025-07-21 © 2025 J.W. Speaker Corporation • Germantown, WI U.S.A. www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660



RELATED PRODUCTS





Part Number 0550271 12-24 DOT/ECE LED RHT High & Low Beam Headlight with FP & 3 Point Mount

Part Number 0550281 12-24 ECE LED LHT High & Low Beam Headlight with FP & 3

Point Mount



Part Number 0550931 12-24 DOT/ECE LED RHT High & Low Beam Headlight with FP & Panel Mount

