PART NUMBER 0555111

# Adaptive LED Headlights – Model 8691 Adaptive 2

## PRODUCT INFORMATION

| | |
|---|---|
| **Description** | 12V DOT/ECE LED High and Low Beam Adaptive Headlight with Black Inner Bezel |
| **Height** | 143.00 mm / 5.63 in |
| **Width** | 143.00 mm / 5.63 in |
| **Depth** | 82.50 mm / 3.25 in |
| **Shape** | Round |
| **Outer Lens Material** | Polycarbonate |
| **Outer Lens Color** | Clear |
| **Housing Material** | Aluminum |
| **Housing Color** | Grey |
| **Bezel Color** | Black |
| **Retrofits** | Pedestal 5 3/4" Round Headlights (PAR46) |
| **Minimum Operating Temperature** | -40 °C / -40 °F |
| **Maximum Operating Temperature** | 65 °C / 149 °F |
| **Connector or Wiring** | Bare Leads |
| **Product Weight** | 3.08 lbs / 1.4 kgs |
| **Shipping Weight** | 2.99 lbs / 1.36 kgs |



8691 ADAPTIVE 2

**Print date: 2026-11-12**

© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.


www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

**PART NUMBER 0555111**

# Adaptive LED Headlights – Model 8691 Adaptive 2

## PRODUCT DIMENSIONS




## ELECTRICAL SPECIFICATIONS

| | |
|---|---|
| **Input Voltage** | 12V DC |
| **Operating Voltage** | 9-16V DC |
| **Transient Spike Protection** | 150V Peak @ 1 HZ-100 Pulses |
| **Black Wire** | Ground |
| **White Wire** | High Beam |
| **Yellow Wire** | Low Beam |
| **Red Wire** | Front Position |
| **Current Draw** | 1.9A @ 12V DC (Low Beam)<br>3.2A @ 12V DC (High Beam)<br>0.21A @ 12V DC (Front Position)<br>4.2A @ 12V DC (Low Beam at Full Lean)<br>5.5A @ 12V DC (High Beam at Full Lean) |

**Print date: 2026-11-12**
© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

PART NUMBER 0555111

# Adaptive LED Headlights – Model 8691 Adaptive 2


## REGULATORY STANDARDS COMPLIANCE





| | |
|---|---|
| Buy America Standards | ECE Reg 113 |
| ECE Reg 50 | Eco Friendly |
| FMVSS 108 s10.1 (Table XX) | IEC IP67 |

## PHOTOMETRIC SPECIFICATIONS

| | |
|---|---|
| **Raw Lumen Output** | 3,520 (High Beam); 2,120 (Low Beam) |
| **Effective Lumen Output** | 1,600 (High Beam); 1,050 (Low Beam) |
| **Candela Output** | 60,000 (High Beam); 8,300 (Low Beam) |
| **Nominal LED Color Temperature** | 5000 K |
| **Beam Pattern(s)** | Forward Lighting - High Beam (DOT/ECE)<br>Forward Lighting - Low Beam (DOT/ECE)<br>Signalization - Front Position |






© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

PART NUMBER 0555111

# Adaptive LED Headlights – Model 8691 Adaptive 2

## APPLICATIONS




## ADDITIONAL INFORMATION

**Improvements over the original Adaptive Series**
The NEW Adaptive 2 Series headlights have been improved to feature Adaptive technology when using the high beam, in addition to the low beam. Providing ditch-to-ditch lighting to eliminate dark corners on sharp turns and a punch of light 1,500 feet down the road to give you a safer and more confident ride.
**Red Wire**
Note about Front Position: The front position light is a requirement outside the United States. **If your bike is operated in the United States you do NOT need to connect this wire (red)** unless your bike is equipped with a front position light.

## PRODUCT WARNINGS

For California residents:
⚠ **WARNING:** Cancer and reproductive harm - www.P65Warnings.ca.gov.
⚠ **AVERTISSEMENT:** Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

## RELATED PRODUCTS



**Part Number 0555121**
12V DOT/ECE LED High and Low Beam Adaptive Headlight with Chrome Inner Bezel

**Print date: 2026-11-12**
© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.