PRODUCT INFORMATION

Description
Height
Width
Depth
Shape
Outer Lens Material
Outer Lens Color
Housing Material
Housing Color
Mounting Hardware Description
Mounting Type
Minimum Operating Temperature
Maximum Operating Temperature
Mating Connector
Product Weight

Shipping Weight

12-24V LED Compact Work Light with Pedestal Mount 76.10 mm / 3 in 98.80 mm / 3.89 in 43.40 mm / 1.71 in Rectangular Polycarbonate Clear Aluminum Black (x1) 5/16"-18 x 1.00" Mounting Bolt Bracket Pedestal -40 °C / -40 °F

65 °C / 149 °F

JAE Connector MX19A003S51 harness included with flying leads 0.40 lbs / 0.18 kgs


7.19 lbs / 3.26 kgs







PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage	12-24V DC
Operating Voltage	9-30V DC
Transient Spike Protection	330V Peak @ 1 HZ-100 Pulses
Red Wire	Power
Black Wire	Ground
Current Draw	2.2A @ 12V DC (Power) 1.0A @ 24V DC (Power)

REGULATORY STANDARDS COMPLIANCE




IEC IP67





PHOTOMETRIC SPECIFICATIONS



APPLICATIONS



PRODUCT WARNINGS

For California residents: ▲ WARNING: Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>. ▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - <u>www.P65Warnings.ca.gov</u>.

ACCESSORIES



Part Number 8201241 DIN Pole Mount for Work Lights



RELATED PRODUCTS



Part Number 1603931 36-80V LED Compact Work Light with Pedestal Mount



Part Number 1603932 36-80V LED Compact Work Light with Pedestal Mount (BULK with Harness)



Part Number 1603951 12-24V LED Compact Work Light with Panel Mount



Part Number 1603971 36-80V LED Compact Work Light with Panel Mount



Part Number 1604241 12-24V LED Anti-Glare, Eco-Friendly Work Light with Pedestal Mount and Harness

