LED Compact Work Light - Model 792

PRODUCT INFORMATION

Description 12-24V LED Compact Work Light with

Panel Mount

 Height
 82.06 mm / 3.23 in

 Width
 98.80 mm / 3.89 in

 Depth
 43.40 mm / 1.71 in

ShapeRectangularOuter Lens MaterialPolycarbonate

Outer Lens ColorClearHousing MaterialAluminumHousing ColorBlackMounting TypePanel

Minimum Operating -40 °C / -40 °F

Temperature

Maximum Operating $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$

Temperature

Mating Connector JAE Connector MX19A003S51 harness


included with flying leads


Product Weight 0.40 lbs / 0.18 kgs Shipping Weight 7.19 lbs / 3.26 kgs






PRODUCT DIMENSIONS









LED Compact Work Light - Model 792

ELECTRICAL SPECIFICATIONS

Input Voltage 12-24V DC 9-30V DC **Operating Voltage**

Transient Spike Protection 330V Peak @ 1 HZ-100 Pulses

Red Wire Black Wire Ground

Current Draw 2.2A @ 12V DC (Power) 1.0A @ 24V DC (Power)

REGULATORY STANDARDS COMPLIANCE









Buy America Standards Eco Friendly IEC IP67 IEC IP69K


PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 3630 **Effective Lumen** 2000 **Output**

Candela Output Nominal LED Color

Temperature

2900 5050 K



LED Compact Work Light - Model 792

APPLICATIONS













PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

ACCESSORIES



Part Number 8201241 DIN Pole Mount for Work Lights

RELATED PRODUCTS



Part Number 1603921 12-24V LED Compact Work Light with Pedestal Mount



Part Number 1603931 36-80V LED Compact Work Light with Pedestal Mount



Part Number 1603932 36-80V LED Compact Work Light with Pedestal Mount (BULK with Harness)



Part Number 1603971 36-80V LED Compact Work Light with Panel Mount



Part Number 1604241 12-24V LED Anti-Glare, Eco-Friendly Work Light with Pedestal Mount and Harness

