PRODUCT INFORMATION

Description 12-24V DOT LED Heated Red Stop, Tail,

& Turn Light Kit with Harness

 Height
 20.28 mm / 0.8 in

 Width
 110.14 mm / 4.34 in

 Depth
 39.53 mm / 1.56 in

Shape Round

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing ColorBlackBezel ColorRedMounting TypeGrommetConnector or WiringBare Leads

Mating Connector 3-Pin AMP Connector (#282087-1)

Product Weight 0.36 lbs / 0.16 kgs Shipping Weight 0.54 lbs / 0.24 kgs

Additional Information Power supplied in any mode will power

the heater. If power is not supplied to the heater, the light will not be heated.


Turn off power before installing.














PRODUCT DIMENSIONS





Pin Out Information



Black Wire (Tail) *Wire harness sold separately on Part # 0346261. Wire harness included on Part # 0346264. Also available as a single accessory (Part # 3270501)

Print date: 2024-04-26

ELECTRICAL SPECIFICATIONS

Input Voltage12-24V DCOperating Voltage9-32V DC

Current Draw 1.2A @ 12V DC (Tail Heated)

1.2A @ 24V DC (Tail Heated) 1.2A @ 12V DC (Turn Heated) 1.2A @ 24V DC (Turn Heated) 1.2A @ 12V DC (Stop Heated) 1.2A @ 24V DC (Stop Heated)

REGULATORY STANDARDS COMPLIANCE













Buy America Standards

idards Eco Friendly

FMVSS 108 s7.1 (Table VII) FMVSS 108 s7.2 (Table VIII)

FMVSS 108 s7.3 (Table IX) IEC IP69K SAE J585 SAE J586

SAE J588

PHOTOMETRIC SPECIFICATIONS

Effective Lumen

Output

54

Beam Pattern(s)

Signalization - Tail

Signalization - Turn (Rear)

APPLICATIONS














SMARTHEAT™ HEATING SYSTEM

The SmartHeat[™] heating system senses ambient temperature and turns the integrated heating system in the lens on & off. This system actually clears ice & snow twice as fast as conventional halogen lamps.

When does the heater turn on?

Heater turns on or off according to temperature changes and vehicle power:

- · Heater will turn on when temperatures drop, generating enough heat to prevent ice build-up.
- Heater will turn on when powering up, de-icing the light as rapidly as possible.

When does the heater turn off?

Heater will turn off when it senses temperatures increase and are above the high temperature threshold.

Learn more about this technology <u>here</u>.

See Additional Information on page 1 for heated wire installation

PRODUCT WARNINGS

For California residents:

▲ **WARNING:** Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

ACCESSORIES



<u>Part Number</u> 4242731

4" Round Rubber Mounting Grommet for Model 234



Part Number **5869401**

4" Round Plastic Mounting Flange for Model 234



Part Number 8200441

4" Round Stainless Steel Trim Ring for Model 234



<u>Part Number</u> 8200451

4" Round Chrome Plastic Trim Ring for Model 234



<u>Part Number</u> 3270501

3-Pin AMP Connector Wire Harness Assembly

Print date: 2024-04-26



RELATED PRODUCTS



Part Number 0346261 12-24V DOT LED Heated Red Stop, Tail, & Turn Light



Part Number 0346421 12-48V DOT LED Non-Heated Stop & Tail Light



Part Number 0346471 12-24V DOT LED Heated White Reverse Light



Part Number 0346474 12-24V DOT LED **Heated White Reverse** Light Kit with Harness



Part Number 0347811 12-24V DOT LED **Heated Amber Turn** Signal



Part Number 0347814 12-24V DOT LED Heated Amber Turn Signal Kit with Harness & Turn Light



Part Number 0347861 12-24V DOT LED Non-Heated Red Stop, Tail,



Part Number 0347864 12-24V DOT LED Non-Heated Red Stop, Tail. & Turn Light Kit with Harness