LED Dome lights & Signal Lights - Model 412

PRODUCT INFORMATION

Description 12-48V ECE LED Front Position & Front

Turn Signal Light

 Height
 165.10 mm / 6.5 in

 Width
 57.15 mm / 2.25 in

 Depth
 27.69 mm / 1.09 in

Shape Rectangular

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing Color Black

Mounting Hardware (x2) M4-0.7 x 16 Mounting Bolts

Description

Mounting TypeLow Profile Mount **Minimum Operating**-40 °C / -40 °F

Temperature

Maximum Operating $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$

Temperature

Connector or Wiring7" Bare LeadsProduct Weight0.33 lbs / 0.15 kgsShipping Weight1.20 lbs / 0.54 kgs

Additional Information Lamp conforms to IP67 when mounting


bolts are torqued to 25 in-lb minimum.





LED Dome lights & Signal Lights - Model 412

PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage 12-48V DC
Black Wire Ground
White Wire Position
Yellow Wire Turn

Current Draw 0.21A @ 12V DC

0.104A @ 24V DC 0.07A @ 36V DC 0.082A @ 48V DC

REGULATORY STANDARDS COMPLIANCE









Buy America Standards ECE Reg 6
ECE Reg 7 Eco Friendly
IEC IP67 UL Recognized

Print date: 2025-07-27

LED Dome lights & Signal Lights - Model 412

PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s) Signalization - Front Position

Signalization - Turn (Front) Signalization - Turn (Rear)

APPLICATIONS























PRODUCT WARNINGS

For California residents:

WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS







<u>Part Number</u> <u>0442511</u>

12-48V Clear LED
Dome Light with 7"
Bare Leads, No Switch,
No Timer

Part Number 0443011

12-48V Clear LED Dome Light with 7" Bare Leads & Switch, No Timer

Part Number 0443301

12-48V Clear LED Dome Light with Deutsch Connector, Switch & 60 Minute Timer

Print date: 2025-07-27

