


LED Headlights - Model 6130 Evolution

PRODUCT INFORMATION

| | |
|----------------------------|--|
| Description | 12-24V DOT/ECE LED RHT High & Low Beam Headlight with Front Position |
| Height | 120.40 mm / 4.74 in |
| Width | 120.40 mm / 4.74 in |
| Depth | 81.53 mm / 3.21 in |
| Shape | Round |
| Outer Lens Material | Polycarbonate |
| Outer Lens Color | Clear |
| Housing Material | Aluminum |
| Housing Color | Black |
| Bezel Color | Black |
| Connector or Wiring | 12" Flying Leads |
| Mating Connector | n/a |
| Product Weight | 1.55 lbs / 0.7 kgs |
| Shipping Weight | 1.68 lbs / 0.76 kgs |



PRODUCT DIMENSIONS



Print date: 2025-02-08

© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
 www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER
 Engineered. Lighting. Solutions.

LED Headlights - Model 6130 Evolution

ELECTRICAL SPECIFICATIONS

| | |
|-----------------------------------|--|
| Input Voltage | 12-24V DC |
| Operating Voltage | 10-30V DC |
| Transient Spike Protection | 150V Peak @ 1 HZ-100 Pulses |
| Black Wire | Ground |
| Yellow Wire | Low Beam |
| White Wire | High Beam |
| Red Wire | Front Position |
| Current Draw | 3.00A @ 12V DC (High Beam) 1.43A @ 24V DC (High Beam) 2.30A @ 12V DC (Low Beam) 1.01A @ 24V DC (Low Beam) 0.12A @ 12V DC (Front Position) 0.09A @ 24V DC (Front Position) |

REGULATORY STANDARDS COMPLIANCE



| | |
|-----------------------------|-------------------------------|
| Buy America Standards | ECE Reg 112 |
| ECE Reg 7 | Eco Friendly |
| FMVSS 108 s10.1 (Table XIX) | FMVSS 108 s10.1 (Table XVIII) |
| IEC IP67 | |

Print date: 2025-02-08


© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER 
Engineered. Lighting. Solutions.

LED Headlights - Model 6130 Evolution

PHOTOMETRIC SPECIFICATIONS

| | |
|-------------------------------|--|
| Raw Lumen Output | 2,230 (High Beam); 1,330 (Low Beam) |
| Effective Lumen Output | 840 (High Beam); 440 (Low Beam) |
| Beam Pattern(s) | Forward Lighting - High Beam (DOT/ECE) Forward Lighting - Low Beam (ECE Right Hand) Signalization - Front Position |



APPLICATIONS



Print date: 2025-02-08

© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

LED Headlights - Model 6130 Evolution

ADDITIONAL INFORMATION

Jump Start: 48V for 2 min
Reverse Polarity: -24V for 2 min
Load Dump: 150V 5 pulses 10 sec intervals
Inductive Switching: 600V 10 pulses 1 sec intervals
Mutual Coupling: 300V 10 pulses 1 sec intervals

PRODUCT WARNINGS

For California residents:

⚠ **WARNING:** Cancer and reproductive harm - www.P65Warnings.ca.gov.

⚠ **AVERTISSEMENT:** Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number

0549891

12-24V ECE LED LHT
High & Low Beam
Headlight with Front
Position

Print date: 2025-02-08

© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER 
Engineered. Lighting. Solutions.