LED ATV and UTV Headlights - Model 8415 Evolution

PRODUCT INFORMATION

Description 12-24V SAE LED Low Beam ATV

Headlight with Fixed Panel Mount

 Height
 119.63 mm / 4.71 in

 Width
 111.25 mm / 4.38 in

 Depth
 72.90 mm / 2.87 in

Shape Round

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing Color Black

Mounting Type Fixed Panel Mount **Minimum Operating** -40 °C / -40 °F

Temperature

Maximum Operating $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$


Temperature

Mating ConnectorPackard 12124817Product Weight0.23 lbs / 0.1 kgsShipping Weight1.10 lbs / 0.5 kgs





PRODUCT DIMENSIONS





LED ATV and UTV Headlights - Model 8415 Evolution

ELECTRICAL SPECIFICATIONS

Input Voltage10-30V DCOperating Voltage12-24V DC

Transient Spike Protection 150V Peak @ 1 HZ-100 Pulses

Current Draw 0.35A @ 12V DC (Low Beam)
0.20A @ 24V DC (Low Beam)

REGULATORY STANDARDS COMPLIANCE







ASABE S608 IEC IP67
SAE J1113-13 SAE J1113-21
SAE J1113-4 SAE J1623


SAE J2258

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 580 Effective Lumen 330

Output

Beam Pattern(s) Forward Lighting - Trapezoid





LED ATV and UTV Headlights - Model 8415 Evolution

APPLICATIONS

















PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number 0551191 12-24V SAE/ECE LED High/Low Beam Light with Xenoy Housing & Adjustable Mount



Part Number 0551761 12-24V SAE/ECE LED High/Low Beam Light with Xenoy Housing & Fixed Panel Mount



0552031 12-24V SAE/ECE LED High/Low Beam Light with Polycarbonate Housing & Adjustable Mount - UL Version



Part Number 0556431 12-24V SAE LED Low Beam ATV Headlight with Adjustable Mount



Part Number 0558361 12-24V DOT LED Low Beam/Front Position Headlight w/ Built in Turn Signal & Adjustable Mount

