# PRODUCT INFORMATION

**Description** 12-24V DOT LED High Speed Heated

Headlight - 2 Light Kit

 Height
 94.50 mm / 3.72 in

 Width
 291.60 mm / 11.48 in

 Depth
 133.20 mm / 5.24 in

Shape Rectangular

Outer Lens Material Polycarbonate

Outer Lens ColorClearHousing MaterialXenoyHousing ColorBlack

**Mounting Hardware** (x4) M8-1.25 x 25 mm OR (x2) 1/2"-13

**Description**x 1.75" SS Carraige Bolt**Mounting Type**Universal Pedestal Mount

**Retrofits** Pedestal Mount Snow Plow Lights


Mating ConnectorDelphi (#12052848)Product Weight9.06 lbs / 4.11 kgsShipping Weight10.21 lbs / 4.63 kgs







## **PRODUCT DIMENSIONS**





### **ELECTRICAL SPECIFICATIONS**

Input Voltage 12-24V DC
Red Wire Front Position
Black Wire Ground
White Wire High Beam
Yellow Wire Turn

Blue Wire Non-Functioning

Orange Wire Low Beam

**Current Draw** 1.75A @ 12V DC (Low Beam)

2.50A @ 12V DC (High Beam) .750A @ 12V DC (Turn)

.040A @ 12V DC (Front Position) 2.00A @ 12V DC (Heater) 1.00A @ 24V DC (Low Beam) 1.50A @ 24V DC (High Beam) .280A @ 24V DC (Turn)

.025A @ 24V DC (Front Position) 1.75A @ 24V DC (Heater)

#### REGULATORY STANDARDS COMPLIANCE










Buy America Standards FMVSS 108 s10.1 (Table XIX)

FMVSS 108 s7.1 (Table VI)

Eco Friendly FMVSS 108 s10.1 (Table XVIII)



### **PHOTOMETRIC SPECIFICATIONS**

Raw Lumen Output 2,880 (High Beam); 2,160 (Low

Beam)

**Effective Lumen** 1,150 (High Beam); 800 (Low

Output Beam)
Candela Output 52,000
Nominal LED Color 5000 K

Temperature


**Beam Pattern(s)** Forward Lighting - High Beam

(DOT)

Forward Lighting - Low Beam

(DOT)

Signalization - Front Position Signalization - Turn (Front)



# **APPLICATIONS**
















## **INSTALLATION & APPLICATION INFORMATION**

Pedestal mount snow plow lights for single or double bolt mounts. Each lamp comes with mounting hardware for single bolt mount included ( $1/2-13 \times 1.75$  SS Carriage Bolt with hex nut and washer), in addition to the 2 M8-1.25 x 25 SS Carriage Bolts for double bolt mounts.



### **ADDITIONAL INFORMATION**

J.W. Speaker's Model 9800 HS is suited for snow plowing, whether "high speed" plowing on highways or residential plowing. Consult with your J.W. Speaker salesperson for more information.

The Model 9800 HS is not designed to be a plug and play for Boss snow plows. If you have a Boss snow plow please see your local Boss dealer for information on the right product to use.

Lamp design integrates acceptance of mating connector Delphi #1205848

### SMARTHEAT™ HEATING SYSTEM

The SmartHeat<sup>™</sup> heating system senses ambient temperature and turns the integrated heating system in the lens on & off. This system actually clears ice & snow twice as fast as conventional halogen lamps.

#### When does the heater turn on?

Heater turns on or off according to temperature changes and vehicle power:

- Heater will turn on when temperatures drop, generating enough heat to prevent ice build-up.
- Heater will turn on when powering up, de-icing the light as rapidly as possible.

#### When does the heater turn off?

Heater will turn off when it senses temperatures increase and are above the high temperature threshold.

Learn more about this technology <u>here</u>.

See Additional Information on page 1 for heated wire installation

#### **PRODUCT WARNINGS**

For California residents:

**WARNING:** Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>.

▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

