


# LED Marine Navigation Lights - Model 450

## PRODUCT INFORMATION

|                                      |  |
|--------------------------------------|--|
| <b>Description</b>                   | 12-24V LED Starboard (Green) Marine Signal Light |
| <b>Height</b>                        | 33.02 mm / 1.3 in                                |
| <b>Width</b>                         | 198.12 mm / 7.8 in                               |
| <b>Depth</b>                         | 43.18 mm / 1.7 in                                |
| <b>Shape</b>                         | Stylized   |
| <b>Outer Lens Material</b>           | Polycarbonate                                    |
| <b>Outer Lens Color</b>              | Clear  |
| <b>Housing Material</b>              | Polycarbonate                                    |
| <b>Housing Color</b>                 | White  |
| <b>Mounting Type</b>                 | Low Profile Mount                                |
| <b>Minimum Operating Temperature</b> | -40 °C / -40 °F                                  |
| <b>Maximum Operating Temperature</b> | 65 °C / 149 °F                                   |
| <b>Connector or Wiring</b>           | 12" Bare Leads                                   |
| <b>Product Weight</b>                | 0.24 lbs / 0.11 kgs                              |
| <b>Shipping Weight</b>               | 1.26 lbs / 0.57 kgs                              |



## PRODUCT DIMENSIONS



Print date: 2026-04-09

© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.  
 www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

**J.W. SPEAKER**  
 Engineered. Lighting. Solutions.

# LED Marine Navigation Lights - Model 450

## ELECTRICAL SPECIFICATIONS

---

|                      |                                  |
|----------------------|----------------------------------|
| <b>Input Voltage</b> | 12-24V DC                        |
| <b>Red Wire</b>      | Positive                         |
| <b>Black Wire</b>    | Negative                         |
| <b>Current Draw</b>  | 0.21A @ 12V DC<br>0.10A @ 24V DC |

## REGULATORY STANDARDS COMPLIANCE

---



ABYC A-16  
Eco Friendly  
USCG COLREGS Part C

Buy America Standards  
IEC IP67


## PHOTOMETRIC SPECIFICATIONS

---

**Nominal LED Color Temperature** 5000 K

## APPLICATIONS

---



## PRODUCT WARNINGS

---

For California residents:

⚠️ **WARNING:** Cancer and reproductive harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

⚠️ **AVERTISSEMENT:** Cancer et effet nocif sur la reproduction - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Print date: 2026-04-09**

© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.  
[www.jwspeaker.com](http://www.jwspeaker.com) • [speaker@jwspeaker.com](mailto:speaker@jwspeaker.com) • 262.251.6660

**J.W. SPEAKER**   
Engineered. Lighting. Solutions.

# LED Marine Navigation Lights - Model 450

## RELATED PRODUCTS

---



**Part Number**  
**0230681**

12-24V LED Port (Red)  
Marine Signal Light

**Part Number**  
**0230701**

12-24V LED Stern  
(White) Marine Signal  
Light