PRODUCT INFORMATION

Description 12-110V LED Red Stripe Zone Light

Height 48.00 mm / 1.89 in Width 150.00 mm / 5.91 in **Depth** 63.00 mm / 2.48 in

Shape Rectangular **Outer Lens Material** Polycarbonate

Outer Lens Color Clear **Housing Material** Aluminum **Housing Color** Black **Bezel Color** Black

Mounting Hardware Description (x1) 5/16"-18 x 1.00" Mounting Bolt

Bracket

Mounting Type Pedestal -40 °C / -40 °F

Minimum Operating

Temperature

Maximum Operating 65 °C / 149 °F

Temperature

Connector or Wiring Deutsch DT04-2P


Mating Connector Deutsch DT06-2S with harness included

with flying leads

Product Weight 0.87 lbs / 0.39 kgs **Shipping Weight** 1.10 lbs / 0.5 kgs



PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage 12-110V DC **Operating Voltage** 9-125V DC

Transient Spike Protection 330V Peak @ 1 HZ-100 Pulses

Black Wire Ground Red Wire Power

 Current Draw
 1.60A @ 12V DC

 0.60A @ 24V DC
 0.52A @ 48V DC

 0.40A @ 80V DC
 0.38A @ 110V DC



REGULATORY STANDARDS COMPLIANCE







Buy America Standards IEC IP67

Tested to ECE Reg. 10 (Radiated Emissions only)

Eco Friendly IEC IP69K

UL Recognized

PHOTOMETRIC SPECIFICATIONS


Raw Lumen Output 1,130 **Effective Lumen** 317

Output

217

Candela Output 3,150

Beam Pattern(s) Warning - Keep Out Zone



APPLICATIONS





RELATED PRODUCTS







Part Number 1603651 12-110V LED Amber Stripe Zone Light



Part Number 1603681 12-110V LED Red Stripe Zone Light with Shroud