PRODUCT INFORMATION

Description 12-24V ECE LED RHT Non-Heated

Headlight - 2 Light Kit

 Height
 94.53 mm / 3.72 in

 Width
 291.58 mm / 11.48 in

 Depth
 133.17 mm / 5.24 in

Shape Rectangular

Outer Lens Material Polycarbonate

Outer Lens ColorClearHousing MaterialXenoyHousing ColorBlackBezel ColorBlack

Mounting Hardware (x4) M8-1.25 x 25 mm OR (x2) 1/2"-13

Descriptionx 1.75" SS Carraige Bolt**Mounting Type**Universal Pedestal Mount

Retrofits Pedestal Mount Snow Plow Lights


Mating ConnectorDelphi (#12052848)Product Weight9.06 lbs / 4.11 kgsShipping Weight10.21 lbs / 4.63 kgs








PRODUCT DIMENSIONS





ELECTRICAL SPECIFICATIONS

Input Voltage 12-24V DC
Operating Voltage 10-32V DC
Red Wire Front Position
Black Wire Ground
White Wire High Beam
Yellow Wire Turn
Blue Wire DRL

Orange Wire Low Beam

2.70A @ 12V DC (Low Beam)
3.40A @ 12V DC (High Beam)
0.85A @ 12V DC (Turn Signal)
0.04A @ 12V DC (Front Position)
1.20A @ 24V DC (Low Beam)
1.60A @ 24V DC (High Beam)
0.27A @ 24V DC (Turn Signal)
0.03A @ 24V DC (Front Position)


REGULATORY STANDARDS COMPLIANCE







Buy America Standards ECE Reg 10
ECE Reg 112 ECE Reg 6
ECE Reg 7 ECE Reg 87
IEC IP67



PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output 2,835 (High Beam); 2,115 (Low

Beam)

Effective Lumen 1,135 (High Beam); 785 (Low

Output Beam)
Candela Output 52,000
Nominal LED Color 5000 K

Temperature

Beam Pattern(s)


ern(s) Forward Lighting - High Beam

(DOT/ECE)

Forward Lighting - Low Beam (ECE

Right Hand)

Signalization - Turn (Front)



APPLICATIONS
















INSTALLATION & APPLICATION INFORMATION

Pedestal mount snow plow lights for single or double bolt mounts. Each lamp comes with mounting hardware for single bolt mount included ($1/2-13 \times 1.75$ SS Carriage Bolt with hex nut and washer), in addition to the 2 M8-1.25 x 25 SS Carriage Bolts for double bolt mounts.



ADDITIONAL INFORMATION

J.W. Speaker's Model 9800 is best suited for normal snow plowing, not "high speed" plowing on highways. Consult with your J.W. Speaker salesperson for more information.

The Model 9800 is not designed to be a plug and play for Boss snow plows. If you have a Boss snow plow please see your local Boss dealer for information on the right product to use.

Lamp design integrates acceptance of mating connector Delphi #1205848

PRODUCT WARNINGS

For California residents:

WARNING: Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number 0550061

12-24V DOT LED Non-Heated Headlight - 2 Light Kit



Part Number

0550171 12-24V ECE LED LHT Non-Heated Headlight - 2 Light Kit



Part Number

0551803 24V DOT LED Heated Headlight - 2 Light Kit



Part Number

0551833 24V ECE LED RHT Heated Headlight - 2 Light Kit





Part Number 0551863 24V ECE LED LHT Heated Headlight - 2

Light Kit





0552243 12V DOT LED Heated Headlight - 2 Light Kit





<u>Part Number</u> <u>0552423</u>

12V ECE LED RHT Heated Headlight - 2 Light Kit





<u>Part Number</u> <u>0552433</u>

12V ECE LED LHT Heated Headlight - 2 Light Kit

