LED Stop, Tail, Turn & Backup Lights - Model 280

PRODUCT INFORMATION

Description 12V LED Stop, Tail, Turn Signal &

Backup Light - GM

 Height
 189.23 mm / 7.45 in

 Width
 49.02 mm / 1.93 in

 Depth
 22.10 mm / 0.87 in

Shape Rectangular

Outer Lens Material Acrylic

Outer Lens Color Clear

Housing Material ABS

Housing Color Black

Mounting TypeLow Profile Mount **Minimum Operating**-40 °C / -40 °F

Temperature


Maximum Operating $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$


Temperature

Connector or WiringPackard (#12124107)Mating ConnectorPackard (#12052848)Product Weight0.28 lbs / 0.13 kgsShipping Weight3.24 lbs / 1.47 kgs



PRODUCT DIMENSIONS





LED Stop, Tail, Turn & Backup Lights - Model 280

ELECTRICAL SPECIFICATIONS

Input Voltage12V DCOperating Voltage9-16V DC

Current Draw 0.105 A @ 12V DC (Stop)

0.020A @ 12V DC (Tail) 0.105A @ 12V DC (Turn) 0.090A @ 12V DC (Backup)

REGULATORY STANDARDS COMPLIANCE









Buy America Standards Eco Friendly IEC IP66 SAE J1455 SAE J1889 SAE J575

UL Recognized

PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s) Signalization - Stop

Signalization - Tail

Signalization - Turn (Front) Signalization - Turn (Rear)

APPLICATIONS



















LED Stop, Tail, Turn & Backup Lights - Model 280

PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

ACCESSORIES



Part Number 3268441

6-Pin PE Connector Wire Harness Assembly

RELATED PRODUCTS



Part Number 0346561 12V LED Stop, Tail, Turn Signal & Backup Light

