LED Strobe Safety Warning Lights - Model 539

PRODUCT INFORMATION

Description 12-80V Green Class III LED Strobe Light

with Flange Mount 66.10 mm / 2.6 in 70.80 mm / 2.79 in 70.80 mm / 2.79 in

ShapeRoundOuter Lens MaterialAcrylicOuter Lens ColorClear

Housing Material Polycarbonate

Housing Color Black

Mounting TypeFlange MountMinimum Operating-40 °C / -40 °F

Temperature

Height

Width

Depth

Maximum Operating 65 °C / 149 °F


Temperature


Connector or Wiring13.5" Bare LeadsProduct Weight0.30 lbs / 0.14 kgsShipping Weight1.51 lbs / 0.68 kgs





PRODUCT DIMENSIONS







LED Strobe Safety Warning Lights - Model 539

ELECTRICAL SPECIFICATIONS

Input Voltage 12-80V DC
Operating Voltage 12-80V DC
Red Wire Positive
Black Wire Negative

Current Draw 0.256A @ 12V DC

0.088A @ 48V DC 0.076A @ 80V DC

REGULATORY STANDARDS COMPLIANCE





Buy America Standards

Eco Friendly

UL Recognized

PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s) Warning - Strobe **Flash Rate 1** 60 +/- 10 fpm

APPLICATIONS




















LED Strobe Safety Warning Lights - Model 539

PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number 0646441 12-80V Amber Class III LED Strobe Light with Flange Mount



Part Number 0646451 12-80V Red Class III LED Strobe Light with Flange Mount



Part Number 0646471 12-80V Blue Class III LED Strobe Light with Flange Mount



Part Number 0646481 12-80V White Class III LED Strobe Light with Flange Mount



Part Number 0647131 12/80V Red/Green LED Indicator Light with Flange Mount