PRODUCT INFORMATION

Description Height Width Depth Shape **Outer Lens Material Outer Lens Color Housing Material Housing Color Bezel Color Mounting Hardware** Description Mounting Type Minimum Operating Temperature Maximum Operating Temperature **Connector or Wiring Mating Connector Product Weight**

Shipping Weight


12V DOT/ECE LED Fog Light 48.40 mm / 1.91 in 150.40 mm / 5.92 in 63.00 mm / 2.48 in Rectangular Polycarbonate Clear **Die-Cast Aluminum** Black Black (x2) 5/16-18 x 1.00" Mounting Bolt Pedestal/Pendant -40 °C / -40 °F 65 °C / 149 °F Integrated 2-Pin Deutsch Connector 2-Pin Deutsch Weather-Proof Plug (DT06-2S) 0.80 lbs / 0.36 kgs

1.20 lbs / 0.54 kgs





PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS

Input Voltage	12V DC
Operating Voltage	10-18V DC
Transient Spike Protection	150V Peak @ 1 HZ-100 Pulses
Red Wire	Power
Black Wire	Ground
Current Draw	0.55A @ 10V DC (Fog) 0.88A @ 12V DC (Fog) 1.10A @ 18V DC (Fog)


REGULATORY STANDARDS COMPLIANCE



Buy America Standards Eco Friendly SAE J578 ECE Reg 19 IEC IP69K SAE J583



PHOTOMETRIC SPECIFICATIONS



PRODUCT WARNINGS

For California residents:

WARNING: Cancer and reproductive harm - <u>www.P65Warnings.ca.gov</u>.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - <u>www.P65Warnings.ca.gov</u>.

ACCESSORIES



Part Number 8201241 DIN Pole Mount for Work Lights



RELATED PRODUCTS







Part Number 1603511 12-24V LED Driving Light

Part Number 1603521 12-24V LED Driving Light with Flood Beam Pattern

Part Number 1603603 12V DOT/ECE LED Fog Light - 2 Light Kit

