## LED Work Light - Model 518

### PRODUCT INFORMATION

**Description** 12-24V LED Work Light with Trapezoid

Beam Pattern & Rubber Shock Mount

 Height
 148.59 mm / 5.85 in

 Width
 207.01 mm / 8.15 in

 Depth
 44.70 mm / 1.76 in

ShapeRectangularOuter Lens MaterialPolycarbonate

Outer Lens Color Clear

Housing MaterialPolycarbonateHousing ColorChrome

Mounting TypeLow Profile MountMinimum Operating-40 °C / -40 °F

**Temperature** 


**Maximum Operating**  $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$ 


Temperature


Product Weight0.75 lbs / 0.34 kgsShipping Weight13.47 lbs / 6.11 kgsAdditional InformationRubber Shock Mount



### **PRODUCT DIMENSIONS**









# LED Work Light - Model 518

#### **ELECTRICAL SPECIFICATIONS**

Input Voltage12-24V DCOperating Voltage9-32V DC

**Transient Spike Protection** 330V Peak @ 1 HZ-100 Pulses

Red Wire Positive

Black Wire Negative

**Current Draw** 1.6A @ 12V DC 0.8A @ 24V DC

### **REGULATORY STANDARDS COMPLIANCE**







**Buy America Standards** 

Eco Friendly

IEC IP69K

#### PHOTOMETRIC SPECIFICATIONS

**Raw Lumen Output** 1,700 **Effective Lumen** 1,000

Output

Nominal LED Color 5000 K

**Temperature** 

**Beam Pattern(s)** Forward Lighting - Trapezoid

#### **APPLICATIONS**






















# LED Work Light - Model 518

#### **PRODUCT WARNINGS**


For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

#### **RELATED PRODUCTS**





12-24V LED Work Light 12-24V LED Flood with Trapezoid Beam Pattern & Low Profile Mount



**Part Number** 1300281

Beam Pattern & Low Profile Mount

