### PRODUCT INFORMATION

**Description** 24V LED Work Light with Medium Flood

Beam Pattern

 Height
 177.55 mm / 6.99 in

 Width
 253.75 mm / 9.99 in

 Depth
 88.90 mm / 3.5 in

 Shape
 Rectangular

Outer Lens MaterialGlassOuter Lens ColorClear

Housing Material Die-Cast Aluminum

**Housing Color** Black

Mounting Hardware Mounting Bolt

Description

Mounting Type Universal Pedestal Mount

**Minimum Operating**  $-40 \, ^{\circ}\text{C} \, / \, -40 \, ^{\circ}\text{F}$ 

**Temperature** 

**Maximum Operating**  $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$ 

**Temperature** 

**Connector or Wiring** Integrated 2-Pin Deutsch Weather-Proof

Socket (DT04-2P)


Mating ConnectorDeutsch DT06-2SProduct Weight6.72 lbs / 3.05 kgsShipping Weight7.50 lbs / 3.4 kgs

Additional Information Wire Harness: JWS part number


3267891.







### **PRODUCT DIMENSIONS**



### **ELECTRICAL SPECIFICATIONS**

Input Voltage24V DCOperating Voltage16-32V DC

**Transient Spike Protection** 330V Peak @ 1 HZ-100 Pulses

Current Draw 3.60A @ 24V DC

#### **REGULATORY STANDARDS COMPLIANCE**







Buy America Standards IEC IP67

Eco Friendly


### PHOTOMETRIC SPECIFICATIONS


Raw Lumen Output 8,100 **Effective Lumen** 3,900

**Output** 

5000 K **Nominal LED Color** 

Beam Pattern(s)





### **APPLICATIONS**



















### **PRODUCT WARNINGS**

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

▲ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.



### **RELATED PRODUCTS**



**Part Number** 0551431 with Medium Flood Beam Pattern



**Part Number** 0551451 12-24V LED Work Light 12-24V LED Work Light 24V LED with Wide with Wide Flood Beam Flood Beam Pattern Pattern



**Part Number** 0557931