


LED Safety Light - Model 560 Warning Projector Light

PRODUCT INFORMATION

Description	12-72V LED Warning Projector Light
Height	118.92 mm / 4.68 in
Width	153.90 mm / 6.06 in
Depth	136.65 mm / 5.38 in
Shape	Rectangular
Outer Lens Material	Acrylic
Outer Lens Color	Clear
Housing Material	Aluminum
Housing Color	Black
Bezel Color	Black
Mounting Hardware Description	Single Carriage Bolt
Mounting Type	Adjustable Mount
Mating Connector	Aptiv 12110293
Product Weight	1.47 lbs / 0.67 kgs
Shipping Weight	1.77 lbs / 0.8 kgs



PRODUCT DIMENSIONS



Print date: 2025-07-24

© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER®
 Engineered. Lighting. Solutions.

LED Safety Light - Model 560 Warning Projector Light

ELECTRICAL SPECIFICATIONS

Input Voltage	12-72V DC
Operating Voltage	10-90V DC
Red Wire	+ Power
White Wire	- Ground
Black Wire	Mode Selection
Current Draw	3.6A @ 12V DC (Mode 0)

REGULATORY STANDARDS COMPLIANCE



ECE Reg 10

PHOTOMETRIC SPECIFICATIONS

Beam Pattern(s)	Warning - Flashing Warning Warning - Keep Out Zone
------------------------	---



Print date: 2025-07-24

© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER®
Engineered. Lighting. Solutions.

LED Safety Light - Model 560 Warning Projector Light

APPLICATIONS



INSTALLATION & APPLICATION INFORMATION

Black Wire is Mode Selection:

Select desired mode by touching black wire to Power + (1-2 sec)

Mode will switch to next state per table below.

Once desired state is set white wire can be removed or capped off.

Lamp will remain in selected mode.

Mode:

Mode Selection 0

Red LED: Steady On, Blue LED: Steady On

Mode Selection 1

Red LED: Flash 60 per min (1Hz), Blue LED: Flash 60 per min (1Hz)

Mode Selection 2

Red LED: Triple flash 60 per min (1Hz), Blue LED: Triple flash 60 per min (1Hz)

Mode Selection 3

Red LED: Flash 60 per min (1Hz), Blue LED: Triple flash 60 per min (1Hz)

Mode Selection 4

Red LED: Flash 200 per min (2Hz), Blue LED: Flash 200 per min (2Hz)

Mode Selection 5

Red LED: Flash 60 per min (1Hz), Blue LED: Steady On

PRODUCT WARNINGS

For California residents:

⚠ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

⚠ AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

Print date: 2025-07-24

© 2025 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER®
Engineered. Lighting. Solutions.

LED Safety Light - Model 560 Warning Projector Light

RELATED PRODUCTS



Part Number
1300661

12-72V LED Universal
Warning Red Projector
Light



Part Number
1300791

12-72V LED Universal
Warning Blue Projector
Light



Part Number
1300801

12-72V LED Pedestrian
Warning Projector
Light