
PART NUMBER 0562081

Model 8800 EVO-X Headlight

PRODUCT INFORMATION

Description	12-24V DOT LED High Beam Heated Headlight with Black Bezel
Height	107.19 mm / 4.22 in
Width	167.64 mm / 6.6 in
Depth	86.57 mm / 3.41 in
Shape	Rectangular
Outer Lens Material	Hardcoated Polycarbonate
Outer Lens Color	Clear
Housing Material	Polycarbonate
Housing Color	Black
Bezel Color	Black
Retrofits	1A1 and 2A1 (4" x 6") Sealed Beams
Minimum Operating Temperature	-40 °C / -40 °F
Maximum Operating Temperature	65 °C / 149 °F
Connector or Wiring	Integrated 6-pin Deutsch to H4 (AMP #172615-2), 10" length
Mating Connector	H4 AMP #172615-2







Print date: 2026-11-11
© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

Model 8800 EVO-X Headlight


PRODUCT DIMENSIONS





PIN	WIRE
1 - Positive	Red
2 - Ground	Black

6-Pin Deutsch



PIN	FUNCTION
PIN 1	
PIN 2	
PIN 3	
PIN 4	Ground
PIN 5	High Beam
PIN 6	

Print date: 2026-11-11
© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

PART NUMBER 0562081

Model 8800 EVO-X Headlight

ELECTRICAL SPECIFICATIONS


Input Voltage	12-24V DC
Operating Voltage	9-32V DC
Red Wire	Power
Black Wire	Ground
Current Draw	5.00A @ 12V DC 2.50A @ 24V DC

REGULATORY STANDARDS COMPLIANCE

ECE Reg 10
FMVSS 108 s10.1 (Table XVIII)
IEC IP69K
ECE Reg 149 - HR
IEC IP67
SAE J1383

PHOTOMETRIC SPECIFICATIONS

Raw Lumen Output	3,425
Effective Lumen Output	1,390
Candela Output	66,000
Nominal LED Color Temperature	5700 K
Beam Pattern(s)	Forward Lighting - High Beam (DOT)



Print date: 2026-11-11

© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.

www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

PART NUMBER 0562081

Model 8800 EVO-X Headlight

APPLICATIONS



PRODUCT WARNINGS

For California residents:
⚠ **WARNING:** Cancer and reproductive harm - www.P65Warnings.ca.gov.
⚠ **AVERTISSEMENT:** Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.

Model 8800 EVO-X Headlight

RELATED PRODUCTS



Part Number 0562021
12-24V DOT/ECE LED RHT Asymmetric Low Beam Headlight with Black Bezel



Part Number 0562031
12-24V DOT/ECE LED RHT Asymmetric Low Beam Headlight with Chrome Bezel



Part Number 0562041
12-24V DOT/ECE LED RHT Asymmettric Low Beam Heated Headlight with Black Bezel



Part Number 0562051
12-24V DOT/ECE LED RHT Asymmetric Low Beam Heated Headlight with Chrome Bezel



Part Number 0562061
12-24V DOT/ECE LED High Beam Headlight with Black Bezel



Part Number 0562071
12-24V DOT/ECE LED High Beam Headlight with Chrome Bezel



Part Number 0562091
12-24V DOT LED High Beam Heated Headlight with Chrome Bezel



Part Number 0562101
12-24V DOT/ECE LED RHT 5-in-1 Headlight with Black Bezel

© 2026 J.W. Speaker Corporation • Germantown, WI U.S.A.
www.jwspeaker.com • speaker@jwspeaker.com • 262.251.6660

J.W. SPEAKER® Engineered. Lighting. Solutions.