## Oval LED Work Lights - Model 7250 XD

## PRODUCT INFORMATION

**Description** 12-24V LED Work Light with Spot Beam

Pattern & Pedestal Mount

 Height
 152.40 mm / 6 in

 Width
 170.18 mm / 6.7 in

 Depth
 68.58 mm / 2.7 in

**Shape** Oval

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing Color Black

**Mounting Hardware** (x1) 3/8-16 x 1.5" Stainless Steel Hex

**Description** Head Bolt **Minimum Operating** -40 °C / -40 °F

**Temperature** 


**Maximum Operating**  $65 \, ^{\circ}\text{C} \, / \, 149 \, ^{\circ}\text{F}$ 


**Temperature** 

Connector or WiringDeutsch DT04-2PMating ConnectorDeutsch DT06-2SProduct Weight0.80 lbs / 0.36 kgsShipping Weight2.80 lbs / 1.27 kgs



## **PRODUCT DIMENSIONS**







# Oval LED Work Lights - Model 7250 XD

## **ELECTRICAL SPECIFICATIONS**

Input Voltage12-24V DCOperating Voltage10-32V DCBlack WireGroundRed WirePower

**Current Draw** 1.60A @ 12V DC

0.90A @ 24V DC

### REGULATORY STANDARDS COMPLIANCE









Buy America Standards CISPR 12
CISPR 22 Eco Friendly
IEC IP69K SAE J1113-13

**UL Recognized** 

### PHOTOMETRIC SPECIFICATIONS


**Raw Lumen Output** 3715 **Effective Lumen** 2174

Output

Nominal LED Color 5700 K

**Temperature** 

**Beam Pattern(s)** Forward Lighting - Spot





# Oval LED Work Lights - Model 7250 XD

## **APPLICATIONS**















## **PRODUCT WARNINGS**

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

#### RELATED PRODUCTS



**Part Number** 1801511 12-24V LED Work Light 12-24V LED Work Light with Trapezoid Beam Pattern & Pedestal Mount



**Part Number** 

1801521 with Flood Beam Pattern & Pedestal Mount

